

9800 AE+ Airborne Satellite Router



Network Configuration

Compatibility	Evolution® and iDirect Velocity™ compatible		
Network Topology	DVB-S2 with Adaptive TDMA Returns		
	Downstream		Upstream
	DVB-S2/ACM		A-TDMA
Modulation	QPSK, 8PSK, 16APSK		BPSK, QPSK, 8PSK
FEC	LDPC 1/4-8/9		2D 16-State, 1/2-6/7
Maximum Rates	Symbol	45 Msps	15 Msps
	<i>Maximum downstream and upstream data rates cannot be achieved simultaneously Maximum rates are achieved with optimal configurations</i>		
Spread Spectrum	Spreading Factor		2, 4 and 8
	Max Chip Rate		15 Mcps

Interfaces

Primary Interface	ARINC 600 Size 2 – per ARINC 791, Part 1		
SATCOM Interfaces	Tx: Size 8 Coax, 950-2050 MHz, Composite Power 0 dBm to -30 dBm Rx: Size 8 Coax, 950-2150MHz, -5 dBm (max) composite to -130+10*Log10(Sym rate) dBm (min) single carrier Software Controllable 10/50 MHz Reference on Tx		
Data Interfaces	LAN: Three Gigabit Ethernet; 1-front (RJ45), 2-back (Size 8 Quadrax) Three 10/100 Mbps Ethernet - rear (Size 8 Quadrax) Console: RS-232		
Discrete Inputs/Outputs	Remote Power Reset, Weight on Wheels, TX Mute In, TX Mute Out, TX Control In, Operator Ground Enable, Maintenance Ground Enable		
CPU Interfaces	USB – front panel		KVM – rear panel
	Serial Com 1 – (RS-232) – rear panel		Serial Com 2 – (RS-485) – rear panel
Protocols Supported	TCP, UDP, ICMP, IGMP, RIPv2, Static Routes, NAT, DHCP, DHCP Helper, Local DNS Caching, OpenAMIP, cRTP		
Security	TRANSEC module (E0002268), AES Link Encryption (256-bit)**, X.509 Digital Certificates, Automatic Key Management, SHIELD		
Traffic Engineering	Group QoS, QoS (Priority Queuing and CBWFQ), Strict Priority Queuing, Application Based QoS, Minimum CIR, CIR (Static and Dynamic), Rate Limiting		
Other Features	Built-in Automatic Uplink Power, Frequency and Timing Control, Authentication, Ultra High-Speed COTM		

Mechanical/Environmental

Size	4MCU per ARINC 600 W 4.88 in x D 15.03 in x H 7.62 in (W 12.40cm x D 38.18cm x H 19.35cm)		
Weight	17 lbs (7.71 kg)		
Operating Temperature	-4° to +158°F (-20° to +70°C) at sea level with temperature gradient of 1°C per 1 min		
Altitude	Operational: Up to 50,000 ft (15,240m)		
Relative Humidity	Max 95% non-condensing humidity (operational)		
Input Voltage	18-36 VDC; nominal 28 VDC		
Power Consumption	DC: 7.0A maximum at 28 VDC		
DO-160G Compliance	Operational Shock/Crash Safety Vibration Temperature and Altitude Explosive Atmosphere Electrostatic Discharge (ESD) Humidity		Power: Input, Voltage Spike, Lightning Induced Transient Susceptibility Audio Frequency Conducted Susceptibility – Power Inputs Induced Signal Susceptibility Radio Frequency Susceptibility Temperature Variation
MIL-STD-461F Compliance	Electromagnetic Interference (EMI)		
MIL-STD-704F Compliance	Aircraft Electrical Power		
Certifications	WGS Certification Pending FIPS 140-2 Level 3 (#3056) - TRANSEC Module		

Unless otherwise specified, the information given above is for the Evolution platform and is software dependent. The activation of some features may require a license or subscription. For more information, please contact your sales representative
*Applies to iDirect Velocity only and is software dependent